# Ball Lock Pins · self-locking, with T-Handle

22340.0041



# **Product Description**

For quick fastening, locking, adjusting, changing and securing. Quickly and easily unlockable for frequently repeated connections.

All versions are corrosion resistant. When using stainless steel 1.4542: high-strength, hardened, abrasion resistant pin with high load capacity.

Version with ergonomic grip.

### **Material**

# Pin part

· Stainless steel 1.4305

#### Handle

Aluminium, black similar to RAL 9005

#### Press button

· Stainless steel, black

# **Spring**

Stainless steel

# Operation

The balls are unlocked by pressing the button.

# Characteristic

Types from stainless steel 1.4542 with marking below the balls.

### More information

#### Notes

Customized design on request.

This product is also available in INCH dimensions.


#### **Accessories**

Can easily be fitted with retaining cable EH 22400.

# **Further products**

- Locating Bushings, for ball lock pins and socket pins
- Locating Bushings, with flange, for ball lock pins and socket pins
- Retaining Cables
- Positioning Bushings, with collar, DIN 172 A
- Positioning Bushings, without collar, DIN 179 A
- Ball Lock Pins with T-Handle, single acting comply with NAS / MS17985

# **Drawing**



Erwin Halder KG

\*\* Types from stainless steel 1.4542 with marking.

www.halder.com Page 1 of 2


Published on: 13.11.2024


# **Order information**

Dimensions									Location hole		I	Shearing resistance,	Art. No.		
<b>d</b> <sub>1</sub> -0.04 -0.08	<b>I</b> <sub>1</sub> +0.6	d <sub>2</sub>	d <sub>3</sub>	1 <sub>2</sub> ±1	l <sub>3</sub>	I <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub>	H11	min.	min. max.		two-shear <sup>1)</sup> min.		
'	[mm]									[°C]		[g]	[kN]		
Stain	Stainless steel														
8	70	9.5	14.7	8.2	35.8	26.9	51.5	15.8	8	-30	150	56	38	22340.0041	

<sup>1)</sup> Shearing resistance similar to DIN 50141

# **Application example**





# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

# Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

Erwin Halder KG

# Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2

Published on: 13.11.2024