Spring Plungers • with pin and internal hexagon - INCH 2B030.0148



Product Description

To be used for positioning, indexing, locking, latching as well as for other similar pressure applications.

Spring plungers can be used for locating or for applying pressure, as a detent or for ejection.

Material

Pin

• Stainless Steel 1.4305 (ASTM-A-582), nitrided

Body

Stainless steel 1.4305 (ASTM-A-582)

Spring

· Stainless steel

Characteristic

Standard spring load: no marking



Heavy spring load

More information

Notes

Customized design on request.

Spring plungers are specially tested for spring range and forces.

· This product is manufactured in INCH dimensions.


References

A conversion table can be found in the technical data following these product information pages. Thread lock: polyamide spot coating (for details please refer to the technical appendix).

Further products

· Spring Plungers, with pin and internal hexagon

Drawing




Order information

Dimensions							Stroke	Spring load ¹⁾		B		Ĭ	Art. No.
d ₁		Thread	d ₂	1		S	F₁ ~	F ₂	min.	max.			
		[in]		[in]		[in]	[in]	[lb]		[°F]		[oz]	
stainless steel, standard spring load, Without thread lock													
3/8-16	3/8	0.375	2A-UNC	0.186	1 1/8	3/16	0.188	2.7	7.2	-22	482	0.33	2B030.0148

1) statistical average value

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.