Spring Plungers • with ball and slot - INCH 2B050.0222



Product Description

To be used for positioning, indexing, locking, latching as well as for other similar pressure applications.

Spring plungers can be used for locating or for applying pressure, as a detent or for ejection.

Material

Body


· Free cutting steel, blackened

Ball

· Stainless steel, hardened

Spring

Stainless steel





Heavy spring load

More information

Characteristic

Notes

Light spring load

Customized design on request.

Spring plungers are specially tested for spring range and forces.

Standard spring load

• This product is manufactured in INCH dimensions.

References


A conversion table can be found in the technical data following these product information pages.

Thread lock: polyamide spot coating (for details please refer to the technical appendix). Calculation of indexing resistance, please refer to appendix - Technical Data -

Further products

- · Spring Plungers, with ball and slot
- · Locators, with bore hole, for spring plungers
- · Locators, smooth, for spring plungers


Drawing



Order information

Dimensions						Stroke	Spring load ¹⁾				Ĩ	Art. No.
d ₁			Thread	d ₂	1	S	F ₁	F ₂	min.	max.		
[in]			[in]		[in]	[lb]		[°F]		[oz]		
free cutting steel, light spring load, With thread lock												
5/8-11	5/8	0.625	2A-UNC	3/8	63/64	0.096	4.5	9	-22	194	0.79	2B050.0222

¹⁾ statistical average value



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 27.06.2024.

Contains Proposition 65 substances

<u>//</u>

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.