# **Taper Clamping Units**

23250.0116



# **Product Description**

Taper clamping units are particularly suitable for horizontal and vertical multiple clampings. The taper clamps are compact in build and therefore enable clamping without geometric interference.

## **Material**

### Body

· Tool steel, hardened, bright

#### Screw

· Heat-treated steel, tempered, quality 12.9

# Spring

· Spring steel wire

## Clamping jaws

· Tool steel, hardened, blackened and ground

## **Assembly**

Can be mounted in a threaded hole or with T-nuts for horizontal or vertical multiple clamping.

## **Operation**

Inserting the socket head screw moves the two clamping chucks outwards and presses the workpieces against a stop. Using the double taper, an additional vertical clamping force will be achieved. Stroke of taper clamping units with M  $5 = \pm 0.5$ , M  $8 = \pm 0.5$ , M  $12 = \pm 1$  and M  $16 = \pm 1.5$ . Can be mounted in a threaded hole or with T-nuts for horizontal or vertical multiple clamping.

## More information

### References

For further taper clamping units, refer to section "Multiple Clamping Systems"


#### Accessories

Nuts for T-Slots (EH 23010.) have to be purchased separately.

## **Further products**

- Nuts for T-Slots, DIN 508
- · Coverings, for taper clamping units
- Taper Clamping Units, plain / ribbed, M8
- · Taper Clamping Units, plain / ribbed, M12
- Taper Clamping Units, with screw fastened thread, M12

## **Drawing**



Erwin Halder KG




www.halder.com Page 1 of 3

Published on: 16.10.2024

# **Order information**

Dimensions						Clamping force	Tightening torque	I	Art. No.
d <sub>1</sub>	I	b <sub>1</sub>	b <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	max.	max.		
[mm]						[kN]	[Nm]	[g]	
double taper, ribbed clamping jaw, two-sided – picture 2									
M16	58 – 66	56	42	50	5	80	210	906	23250.0116

# **Application example**





Page 2 of 3 Published on: 16.10.2024

# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

## **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

## **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 3 of 3

Published on: 16.10.2024