## **Knurled Nuts •** DIN 6303

# 24480.0210



## **Product Description**

#### **Material**

• Stainless steel 1.4305

#### **Assembly**


Form B: after being bored through the pin hole is to be situated within the tolerance field H7.


#### More information

#### **Notes**

Knurling pitch and knurling depth may differ from DIN.

## Drawing





picture 1


picture 2

Erwin Halder KG

### **Order information**

Dimensions							I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d₄	h	k	t	_	
[mm]							[g]	
without pin hole, form A – picture 1, Stainless steel								
M10	36	28	30	20	14	8	83	24480.0210

## **Application example**



Page 1 of 2 www.halder.com Published on: 10.8.2024

### Compliance

### **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

#### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 27.06.2024.

#### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 2 of 2

Published on: 10.8.2024