# **Rubber Endstop Buffers** • low structure

### 25150 1166



# **Product Description**

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70  $\pm 5^{\circ}$  Shore A.

### **Material**


### Support washer

Steel, zinc-plated by galvanization, passivated


### Body

NBR

# **Drawing**









picture 2

### **Order information**

d <sub>1</sub>						Spring rate R	Load capacity max.	Spring range	min.	max.	ă	Art. No.
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore – picture 1												
64	26	6	11	2.5	1.1	616	3700	6	-30	120	141	25150.1166

# **Application example**







www.halder.com Page 1 of 2
Published on: 10.8.2024

# Compliance

# **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 27.06.2024.

### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2
Published on: 10.8.2024

Erwin Halder KG