# Rubber Endstop Buffers • low structure

# 25150.1266



# **Product Description**

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70  $\pm 5^{\circ}$  Shore A.

#### **Material**


#### Support washer

Steel, zinc-plated by galvanization, passivated


#### **Body**

• NBR

### **Drawing**



picture 1





picture 2

### **Order information**

$\begin{array}{c c c c c c c c c c c c c c c c c c c $					S <sub>2</sub>	Spring rate R	Load capacity max.	Spring range	min.	max.	Ä	Art. No.
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore and adhesive pad – picture 2												
64	26	6	11	2.5	1.1	616	3700	6	-30	120	149	25150.1266

# **Application example**







www.halder.com Page 1 of 2
Published on: 10.8.2024

# Compliance

# **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 27.06.2024.

#### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2
Published on: 10.8.2024

Erwin Halder KG